

### Features

- High contrast color TFT LCD display supports 1920 x 1080 resolution
- Elegant design with slim bezel
- Long lasting product cycle-enclosure controlled, future generation panels phased-in without external changes.
- Advanced OSD control for picture quality adjustment
- Available with 5-Wire Resistive touch screen
- VESA mount, OEM mounting design

### Application

- Embedded display Unit
- Industrial automation LCD panel
- Gaming, Lottery & Amusement Display
- Touch screen display panel
- Hospitality Display



SPECIFICATION		
Display	Display Type	TFT LCD
	Display Size	21.5 inch diagonal
	Display Area	476.6 (H) x 268.1 (V) mm
	Pixel Pitch	0.2 (H) x 0.2 (V) mm
	Max. Resolution	1920 x 1080
	Colors	16.7M
	Brightness	250 cd/m <sup>2</sup>
	Response Time	3.5 ms (Typ.)
	Viewing angle	170° (H) x 160° (V)
	Contrast Ratio	1000:1
	Backlight Life	30,000 hrs (Min.) / LED
Touch Screen	Technology	5-wire resistive touch
	Type	USB A or RS-232
	OS Support	Windows XP, Vista7, 8, XPe and Linux
Signal Input	Video	VGA & DVI-D
Audio Output	Speaker	2 speakers, 1W/Channel
Power Input	Aadptor	Universal power adaptor Input AC 100~240V, 50~60Hz Output DC 12V / 5A, 60W
	DC in	DC24V (optional)
Certification	EMC Compliance	CE, FCC
Environments & Dimension	Compliance	RoHS II, WEEE
	Operating Temperature	0°C~50°C (32°F~121°F)
	Storage Temperature	-20°C~60°C (-4°F~140°F)
	Relative Humidity	10%~90% non-condensing
	Mounting	VESA 100 x 100mm
	Dimension ( W x H x D )	585 x 500 x 210mm
	Weight	5kg

All Specifications and photo are subject to change without notice

NO150811