

Features

- High contrast color TFT LCD display supports resolution up to 1024 x 768
- Zero-Bezel for seamless design, IP65 rated
- Projected capacitive touch screen, with Multi touch
- Advanced OSD control for picture quality adjustment
- Streamlined cable management
- VESA mount, OEM mounting design

Application

- Embedded display unit
- Industrial automation LCD panel
- Gaming, Lottery & Amusement Display
- Touch screen display panel
- Medical, healthcare, government, retail product selector, hospitality Display,
- Aviation simulators, Industrial test equipment, and Instrumentation



SPECIFICATION		
Display	Display Type	TFT LCD
	Display Size	15 inch diagonal
	Display Area	304.1 (H) x 228.1 (V) mm
	Max. Resolution	1024 (W) x 768 (H)
	Colors	16.7M
	Brightness	350 cd/m ²
	Response Time	8 ms (Typ.)
	Viewing angle	160° (H) x 160° (V)
	Contrast Ratio	800:1
	Backlight Life	50,000 hrs (Min.) / LED
Touch Screen	Technology	10-point projected capacitive touch
	Type	USB
	OS Support	Windows XP, Vista7, 8, XPe and Linux
Signal Input	Video	VGA
	Audio	1 x 3.5mm Audio Jack 1 x 2W speaker
	USB	1 x USB Type A to Type B
Power Input	Aadpter	Input AC 100~240V, 50~60Hz Output DC 12V / 3A, 36W
Certification	EMC Compliance	CE, FCC, BSMI, VCCI, LVD, CCC
Environments & Dimension	IP Level	IP65 front panel compliant
	Compliance	RoHS II, WEEE
	Operating Temperature	0°C~40°C (32°F~104°F)
	Storage Temperature	-20°C~60°C (-4°F~140°F)
	Relative Humidity	20%~80% non-condensing
	Mounting	VESA 75 x 75mm
	Dimension (W x H x D)	351.0 x 314.5 x 140.0mm
Weight	3.8 kg	

All Specifications and photo are subject to change without notice

NO160322