

### Features

- Rugged metal offering strong protection
- High contrast color TFT LCD display supports resolution up to 1920 x 1080
- Compatible with VGA, IBM and VESA signal standards
- Advanced OSD control for picture quality adjustment
- Optional 5-Wire Resistive / Projected Capacitive / Infrared touch screen
- Optional High Brightness Display / Wide Temperature / IP65
- Various Mounting options: VESA, Panel mount

### Application

- Embedded display Unit
- Industrial automation LCD panel
- Gaming, Lottery & Amusement Display
- Touch screen display panel
- Kiosks, Arcade games, Hospitality Display, ATM Machines
- Aviation simulators, Industrial test equipment, and Instrumentation




SPECIFICATION		
Display	Display Type	TFT LCD
	Display Size	32 inch diagonal
	Display Area	498.4 (H) x 392.8 (V) mm
	Max. Resolution	1920 x 1080
	Colors	16.7M
	Brightness	400 cd/m <sup>2</sup>
	Response Time	8 ms (Typ.)
	Viewing angle	178° (H) x 178° (V)
	Contrast Ratio	4000:1
	Backlight Life	50,000 hrs (Min.) / LED
Touch Screen	Technology	5-wire resistive touch Projected capacitive touch Infrared touch
	Type	USB A or RS-232
	OS Support	Windows XP, Vista7, 8, XPe and Linux
	Signal Input	Video (Optional)
Power Input	Aadptor	Internal power supply with universal / Auto-Sensing AC 100~240V, 50~60Hz
Certification	EMC Compliance	TBD
Environments & Dimension	IP Level (Optional)	IP65 front panel compliant
	Compliance	RoHS II, WEEE
	Operating Temperature	0°C~50°C (32°F~121°F)
	Storage Temperature	-20°C~60°C (-4°F~140°F)
	Relative Humidity	10%~90% non-condensing
	Mounting	VESA 100 x 100mm + Panel Mount
	Dimension ( W x H x D )	738 x 439.6 x 73.5mm
Weight	12kg	

All Specifications and photo are subject to change without notice

NO160121

## Dimensions



All Specifications and photo are subject to change without notice

NO160121